

Expert Power Control 8012



8

8-fold switched PDU with IEC Locks

Rear view: IEC-Lock sockets prevent accidental disconnection of IEC cables



Features

- 8 Power Ports individually switchable directly on the device, via HTTP, command line tool and RS232 serial interface
- Status and Power-up delay (0...9999 seconds) adjustable individually for each Power Port after power blackout
- Latency time of 1 second prevents simultaneous power-up of multiple Power Ports
- Programmable turn-on/turn-off sequence
- Interface for optional sensors for environmental monitoring
- Firmware update via Ethernet during operation
- HTTP 1.1, DHCP, SNMPv1 (Traps), SNMPv2c (Traps), Syslog
- Access control via IP Access Control List
- Access control via optional HTTP password
- Low internal power consumption, max. 5 W
- Developed and manufactured in Germany

Electrical Connections

- 1 power supply (IEC C20, max. 16 A)
- 8 Power Ports (IEC-Lock C13, max. 10 A)
- Ethernet connector RJ45 (10/100 Mbit/s)
- Serial interface RS232 (Sub-D 9-pin)
- RJ11 connector for optional temperature sensor

Technical Details

- Dimensions: 19 inch, 1 rack unit
- LxHxD: 43.9 x 4.4 x 15.0 cm (without brackets)
- Weight: ca. 2.3 kg
- Operating temperature: 0-50 °C
- Storage temperature: -20 - 70 °C
- Relative humidity: 0 - 95 % (non-condensing environment)

Order code	Product	Feature	Operating Voltage	Maximum Current
8012	Expert Power Control 8012	Power connectors on rear panel, IEC-Lock sockets	230 V	16 A
7000	Temperature Sensor 7000	-20°C to +80°C		
0807	Cable Holder 0807	13 fixation bridges for load cables		



Gude Analog- und Digitalsysteme GmbH
Eintrachtstr. 113
50668 Koeln, Germany

T +49.221.912 90 97
F +49.221.912 90 98

mail@gude.info
www.gude.info

made
in
Germany