

EL-5500-HBT

8 x 4 HDBaseT™ / HDMI / VGA Presentation Switch (With switchable digital bypass output)




The EL-5500-HBT is an advanced rack mountable HDBaseT, HDMI, VGA, Composite, and Component presentation switcher. This device can scale and switch eight input sources to its two HDMI outputs and a single HDBaseT output, with their associated audio signals to the native resolutions supported by the connected display. This presentation switch also features a switchable digital bypass output allowing any HDMI or HDBaseT input to be directly bypassed via the HDMI bypass output.

Control is via the IR remote, RS-232, IP, or via manual selection buttons. Both digital and analogue stereo audio is supported via a built-in DAC (Digital to Analogue Converter) and ADC (Analogue to Digital Converter) providing flexible audio signal integration. The EL-5500-HBT is the perfect solution for any educational or commercial environment requiring integration of multiple sources and signal formats to two HDMI displays.

FEATURES

- HDMI, HDCP, and DVI compliant
- Digital to Analogue & Analogue to Digital Audio conversion (DAC/ADC)
- Supported Resolutions : HDTV: 480i to 1080p PC: VGA to WUXGA
- Aspect Ratio Adjustment
- Motion Adaptive De-interlace (3D)
- Video Noise Reduction
- Underscan / Overscan Selection
- Picture Adjustment Settings
- HDBaseT Input/Outputs support PoE (Power over Ethernet) through to compatible connected receiver
- Independent HDMI bypass output (switching digital inputs only)
- Supports HDBaseT LAN Serving function
- Supports IR/RS-232/IP and front panel button control



SPECIFICATIONS

Inputs 4x HDMI [4x HDMI Uncompressed AV and Data]
4x 3.5mm Stereo mini-jack [4x Analogue inputs for HDMI Stereo(L/R)]
2x RJ45 [2x HDBaseT HDMI & Propriety Data]
1x 15pin Dsub [1x PC RGBHV]
1x 3.5mm Stereo mini-jack [1x Analogue input for PC Stereo(L/R)]
1x RCA [1x Composite]
2x RCA [1x Analogue input for Composite Stereo (L/R)]
1x RJ45 [1x LAN Serving]
1x 9pin Dsub [1x RS-232 Data]
1x 3.5mm Stereo mini-jack [1x Infra Red Receiver]
1x USB Type A [1x Service Port 1 Propriety Data]
1x USB Mini B [1x Service Port 2 Propriety Data]
1x 3.5mm Stereo mini-jack [1x Service Port 3 Propriety Data]

Outputs 2x HDMI [2x HDMI Uncompressed AV and Data]
1x RJ45 [1x HDBaseT HDMI & Propriety Data]
1x RCA [1x Coaxial 2 Channel LPCM]
1x 3.5mm Stereo mini-jack [1x Analogue Stereo(L/R)]
1x HDMI [1x HDMI Bypass Uncompressed AV and Data]
1x 3.5mm Stereo mini-jack [1x Analogue Bypass Stereo(L/R)]
Dimensions 440mm [W] x 440mm [D] x 50mm [H]
Net Weight 3200g
Gross Weight 4460g

2014-05

Ein Vertriebsprodukt von / Distributed by:

VIDELCO Europe Limited – Professionelle Audio-, Video-, Medien-Technik
Telefon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu


VIDELCO
Europe Limited