




USB 2.0 Ranger® 2304-LAN

4-Port USB 2.0 Ethernet LAN Extender System

4-Port USB 2.0 Ethernet LAN Extender System

The PMD USB 2.0 Ranger 2304-LAN provides the ability to connect USB 2.0 devices to hosts across a Ethernet Local Area Network using existing cabling.



LEX



REX


FEATURES

The PMD USB Ranger 2304-LAN extends USB 2.0 peripherals such as flash drives, keyboards, mice, and interactive whiteboards across a Local Area Network (LAN) and supports modern USB 3.0 controllers. Isochronous devices (such as webcams) are not supported by the PMD USB Ranger 2304-LAN.

- Extends USB through 100Mbps or 1000Mbps LANs
- USB 2.0 throughput up to 480Mbps*
- Pre-paired networked configuration** for simple installation
- Supplies up to 600mA to each USB port concurrently

Includes the ExtremeUSB® suite of features:

- True plug and play; no software drivers required
- Supports all major operating systems: Windows®, Mac OS X®, and Linux®
- Reliable operation with supported USB devices, and hubs
- Patented USB extension technology



86341501

Ein Vertriebsprodukt von:

VIDELCO Europe Limited – Professionelle Audio-, Video-, Medien-Technik

Telefon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu





USB 2.0 Ranger® 2304-LAN

4-Port USB 2.0 Ethernet LAN Extender System

APPLICATIONS

- Remote storage
- Video matrix systems
- Interactive whiteboard
- Keyboard and mouse

SPECIFICATIONS

RANGE

Direct Connect:	Up to 100m (330 ft) over solid core Cat 5e or better
Network Connect:	Up to 100m (330 ft) between switches over solid core Cat 5e

USB DEVICE SUPPORT

Maximum Throughput:	Up to 480Mbps*
Traffic Types:	Interrupt, Bulk and Control**
Device Types:	HID (Mouse and Keyboard), Hubs, Storage Devices**

NETWORKING

Standards:	100BASE-T and 1000BASE-T*
Data Traffic:	Layer 2

LEX (LOCAL EXTENDER)

USB Connector:	1 x USB Type B Receptacle
Link Connector:	1 x RJ45
Dimensions:	100mm x 76mm x 26mm (3.9" x 3.0" x 1.0")
Enclosure Material:	Silver Anodized Aluminum

REX (REMOTE EXTENDER)

USB Connectors:	4 x USB Type A Receptacles
Link Connector:	1 x RJ45
Dimensions:	100mm x 76mm x 26mm (3.9" x 3.0" x 1.0")
Enclosure Material:	Silver Anodized Aluminum
Available Current:	Up to 600mA to each USB port
Power Supply:	100-240V AC input, 1A 24V DC Output

ENVIRONMENTAL

Operating Temperature:	0°C to 50°C (32°F to 122°F)
Storage Temperature:	-10°C to 60°C (14°F to 140°F)
Operating Humidity:	20% to 80% relative humidity, non-condensing
Storage Humidity:	10% to 90% relative humidity, non-condensing

COMPLIANCE

EMC:	FCC (Class B), CE (Class B)
Environmental:	RoHS2 (CE)

Specifications subject to change without notification.



**EXTREME
USB®**

ORDER INFORMATION

The PMD USB Ranger® 2304-LAN system includes a LEX, REX, USB Cable, Quick Start Guide, international power adapter with country specific power cord.

86341501

Ein Vertriebsprodukt von:

VIDELCO Europe Limited – Professionelle Audio-, Video-, Medien-Technik

Telefon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu

VIDELCO
Europe Limited