




### Avonic Recorder HDMI to USB

The Avonic AV-REC100 is an easy to use HDMI recorder. It records any source up to 1080p60 including audio to a USB hard disk drive or a High Speed flash drive. Recorded video can be played back on the device itself or through any media player, Blu-Ray Disc player or PC/Notebook that supports AVCHD M2TS file format.

The AV-REC100 is easy to use for everybody, simply insert a USB flash drive and press record. Once you are done, press record again to stop recording and remove the flash drive containing the recording.



## **Features**

Inputs: HDMI

Outputs: HDMI loopout, USB-storage

- High Definition input resolutions up to 1080p60
- Record video & audio and capture photo to 1 USB storage device
- Playback video and photo from USB storage device on-line
- Delete and rename the record file by remote control
- One-button-record to easy operate, no need to install any drivers
- The HDMI video capture formats using the FAT32 file system format
- Maximum file size is 4Gb, seamless recording to next file and maximum disk size 32Gb
- Depending on image complexity, about 1 hour on 4Gb storage
- Rackmount design for professional use with front access

# **Applications**

• Education • Video Conferencing • Broadcasting • Live Events

• Churches • Healthcare • Courtroom • And more

Distributor / Vertrieb:



# Specifications

### Product

Input  1x HDMI Type A  Output  1x USB2.0, (2nd USB is for USB powered HDD)  HDMI, HDCP  HDMI 1.4b, HDCP 1.4
HDD)
HDMLHDCP HDML14b HDCP14
HDMI Input Formats up to 1080p60
Color Space RGB, YCbCr 4:4:4, YCbCr 4:2:2
Color Depth 10-bit, 12-bit
Audio  PCM 2CH, LPCM 5.1, LPCM 7.1, Dolby Digital, DTS 5.1, Dolby Digital+ESD

### Recorded File

Video Bitrate	Variable Bit Rate
Video Resolution	Max 1920x1080
Video Frame Rate	Max 30 fps
Audio Bitrate	768 kbps
Audio Sample Rate	24 kHz

### General specifications

Input voltage	DC5V2A
Power consumption	10W(max), 5W (nominal)
Power supply	5V2A
Power connector	EIAJ-3 - Philmore 275 plug
Operating temperature	0°C ~ 40°C
Storage temperature	-20°C ~ 60°C
Operating humidity	20% ~ 90% RH (non-condensation)
Color	Black
Dimensions product	13 x 8 x 2 cm
Weight product	0.300 kg
Dimensions box	51 x 16 x 10 cm
Weight box	1.0 kg
Included	CM-REC100, PSU, 5V2A Remote Control, Rack mount 1U



Version 1.0

Distributor / Vertrieb:

