
DVDO AIR 2K

Experience Unparalleled Wireless HDMI



DVDO Air - Software Upgradable to Keep You Connected with the Latest Formats



Product Overview

Air 2K makes it easy to connect 2K video in locations where wire runs might be difficult or impossible. By transmitting HD content with near zero lag time between the source and display, Air 2K delivers cable-like reliability. Leveraging advanced radar technology used in fighter aircraft, Air 2K's 60GHz phased-array beam-forming technology automatically scans the room and looks for the best path from transmitter to receiver in every frame of video – up to 60 times a second – making the system free from interference. Comparatively, 2.4GHz and 5GHz-based Wi-Fi networks are subject to frequent interference, have no ability to heal the signal if disturbed, and are forced to compress video to fit in their available bandwidth. Based on SiBeam's 60GHz WirelessHD technology Air 2K is specifically designed with up to a 3Gb/s data rate. With this professional grade technology Air2K will reduce installation time and eliminate call-backs. DVDO also includes an exclusive wireless configuration utility that allows for signal strength indication and software upgrades.

Key Features

- · 60GHz WirelessHD Technology
- · HDMI Connectivity supporting 1080p60 resolution
- · USB powered
- · 30'+ in-room connection
- · 100' line-of-sight connection
- · Exclusive pro-installation software
- · RF "beam" steering for auto-healing connection
- \cdot Free from other Wi-Fi interference
- · Low latency almost zero lag time
- · 7.1 HD audio
- · 3D support
- · CEC pass through
- Fast recovery
- · Easy installation: 10+ mouning options
- · Bounce off walls for hidden installation

Technical Specifications

НДМІ	
Transmitter Unit	1
Receiver Unit	1
Maximum Video Resolution	1080p/60 4:4:4, 12 bit
Audio Formats	7.1ch PCM audio up to 192kHz,
	DTS-HD Master Audio 7.1ch up to
	96kHz, and 5.1ch to 192kHz
Wireless Standard	WiHD 1.1 (60GHz)
Range	30+ ft (10+ m); 100 ft line of sight
Power Supply	5V/1A (Transmitter & Receiver)
	100-240VAC @ 50/60Hz
Active Power	3W Typ. (Transmitter & Receiver)
Radiated Power	(EIRP) 28dBm (630mW)
Mounting Options	Included Base Stand
Dimension (L x W x D)	
Transmitter Unit	3.5" x 2.5" x 1"
Receiver Unit	3.5" x 2.5" x 1"
Package	10" x 5" x 5"
Weight	
Package	2.5 lbs

DVDO® and the family of DVDO products are registered trademarks of DVDO, Inc. in the United States and/or other countries. HDMI® and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and/or other countries. WirelessHD® and the WirelessHD logo are trademarks, registered trademarks or ser vice marks of SiBEAM, Inc. in the United States and/or other countries. All other trademarks and registered trademarks are the property of their respective owners in the United States and/or other countries.

