


DVDO AIR 4K

Experience Uncompressed Wireless HDMI



Experience wireless HDMI with no compromises

Interference Free • Near Zero Latency
 4K30 • 60 GHz RF • Up to 10 meters
 • 7.1 HD Audio • 3D • CEC



HDMI Source



TV

Product Overview

60 GHz WirelessHD Based on SiBeam's 60GHz WirelessHD technology, Air 4K transmits HD content with near zero lag time between the source and display, delivering cable-like reliability. Leveraging advanced radar technology used in fighter aircraft, Air 4K phased-array beam-forming technology automatically scans the room and looks for the best path from transmitter to receiver in every frame of video - up to 60 times a second. Free from Interference 2.4GHz and 5GHz based Wi-Fi networks are subject to frequent interference have no ability to heal themselves if disturbed, and are forced to compress video to fit in their available bandwidth. Air 4K is specifically designed with up to a 3Gb/s data rate and professional grade technology to save valuable installation time, eliminate call-backs, and provide the cool-factor customers are looking for. Exclusive Configuration Software DVDO's wireless configuration utility allows for software upgrades if needed.

Key Features

- 60GHz WirelessHD Technology
- HDMI Connectivity supporting 4K30 resolution
- USB powered
- 30'+ in-room connection
- 100' line of sight
- Exclusive pro-installation software
- RF "beam" steering for auto-healing connection
- Free from other Wi-Fi interference
- Low latency – almost zero lag time
- 7.1 HD audio
- 3D support
- CEC pass through
- Fast recovery
- Easy installation: 10+ mouning options
- Bounce off walls for hidden installation

Technical Specifications

HDMI	
Transmitter Unit	1
Receiver Unit	1
Maximum Video Resolution	4K30
Audio Formats	7.1ch HBR/PCM audio up to 192kHz, Dolby/DTS 5.1 up to 48kHz
Wireless Standard	WiHD 1.1 (60 GHz)
Range	30+ ft (10+ m); 100 ft line of sight
Power Supply	5V/1A (Transmitter & Receiver) 100-240VAC @ 50/60Hz
Active Power	3W Typ. (Transmitter & Receiver)
Radiated Power	(EIRP) 28dBm (630mW)
Mounting Options	Included Base Stand
Dimension (L x W x D)	
Transmitter Unit	3.5" x 2.5" x 1"
Receiver Unit	3.5" x 2.5" x 1"
Package	10" x 5" x 5"
Weight	
Package	2.5 lbs

Ein Vertriebsprodukt von / Distributed by:

VIDELCO Europe GmbH – Professionelle Audio-, Video-, Medien-Technik

Fon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu