

HDBaseT™ LITE Transmitter (60m)

4K, HDCP2.2, HDMI2.0, PoH

PUV-1210PL-TX



4K 3D HDMI2.0 HDBT HDCP2.2 PoH OAR

The PUV-1210PL-TX Transmitter enables transmission of video resolutions up to 4K UHD, along with HD audio, 2-Way IR, RS-232, PoH (Power over HDBaseT) up to 60m.

This solution provides advanced signal management ensuring reliable results in the most demanding installation environments. All audio, video, control, and power are transmitted simultaneously over a single CAT6a/7 cable up to 60m.

SPECIFICATIONS

Input:	1x HDMI Uncompressed AV and Data [1x HDMI] 1x Infra Red Receiver [1x 3.5mm Stereo mini-jack] 1x RS-232 Data [1x 9pin Dsub]
Output:	1x HDBaseT HDMI & Proprietary Data [1x RJ45] 1x Infra Red Emitter [1x 3.5mm Stereo mini-jack]
Power:	48V/0.83A DC (US/EU standards, CE/FCC/UL certified)
Dimensions:	116mm (W) x 106mm (D) x 27mm (H)
Gross Weight:	540g
Net. Weight:	357g

FEATURES

- HDCP2.2 Compliant
- High-Definition video and audio, PoH (Power over HDBaseT) and control (Bi-Directional IR & RS-232 pass through)
- Supported resolutions VGA~WUXGA, 480i~1080p, 4K UHD@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2), 4K UHD@ 60Hz (YUV 4:2:0), 4K/2K@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2) and 4K/2K@ 60Hz (YUV 4:2:0) dependent upon the output display's EDID settings
- 4K/2K & 4K UHD signals can be transmitted up to 35m via CAT5e/6 and 60m via CAT6a/7
- Supports pass-through of HD audio formats: LPCM 2/5.1/7.1CH, Dolby Digital 2/5.1CH, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos and DTS-HD Master Audio
- Supports HDCP repeating and CEC functions
- Support 3D signals
- Compatible with PUV-1210PL-RX Receiver



Vertrieb / Distributor:

VIDELCO Europe GmbH – Professionelle Audio-, Video-, Medien-Technik
Fon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu


VIDELCO
Europe GmbH