

HDBaseT™ Receiver & 4K Dual HDMI Scaler (100m)

4K, HDCP2.2, PoH, LAN, OAR

PUV-1550S-RX



4K

HDMI2.0

HDBT2.0

5Play

HDCP2.2

PoH

OAR

ARC

The PUV-1550S-RX Receiver supports video resolutions up to 4K UHD along with HD audio, 2-Way IR, RS-232, PoH (Power over HDBaseT), LAN and Optical Audio Return (OAR) over a single Cat5e/6/7 cable up to 100m. While the HDBaseT input is limited to a maximum of 4K@60Hz (4:2:0), this unit can automatically convert or scale the input to display 4K@60Hz (4:4:4) at the receiving end depending on the detected capability of the connected display panel. Conversely the user can downscale 4K UHD content to 1080p for simple integration of older displays. A useful troubleshooting feature of PUV-1550S-RX is a 6G UHD HDMI Pattern Generator for testing locally connected displays.

In addition to the full 5Play™ convergence, digital OAR (Optical Audio Return) provides users the ability to transmit Optical Audio (48kHz) to the HDBaseT TX. The RX also features a analogue audio output providing users with total audio flexibility. The PUV-1550S-RX also has on board EDID Management which is useful when troubleshooting connected displays.

SPECIFICATIONS

Input:	1x RJ45 [1x HDBaseT HDMI & Proprietary Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Receiver] 1x Phoenix (3 pin) [1x RS-232] 1x Toslink [1x OAR - Optical Audio Return 2 Channel LPCM]
Output:	2x HDMI [2x HDMI Uncompressed AV and Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Emitter] 1x Phoenix (5 pin) [1x Analogue Audio Analogue Stereo (Balanced or Unbalanced)] 1x RJ45 [1x LAN Serving]
Power:	5V/2.6A DC (US/EU standards, CE/FCC/UL certified)
PoE Power:	Power over HDBaseT
Dimensions:	117mm [W] x 231mm [D] x 25mm [H]
Gross Weight:	610g
Net. Weight:	1066g

FEATURES

- HDBaseT 5Play™ convergence: High-Definition video and audio, 100BaseT Ethernet, PoH (Power over HDBaseT) and control (Bi-directional IR/RS-232 pass-through)
- 4K@60Hz (YUV 4:2:0) signals can be transmitted up to 100m via Cat.6a/7 cable and up to 70m via Cat.5e/6 cable
- HDCP 2.2, HDMI 2.0 and DVI compatible
- Bypasses signal on both HDMI outputs or output B can upscale 1080p signals to 4K and output A can downscale a 4K signal to 1080p (same framerate is maintained)
- Supports automatic 4K@60Hz YUV 4:2:0 to RGB/YUV 4:4:4 conversion for HDMI outputs
- Support signal bypass on HDMI output
- Supports data rates up to 18Gbps (6G) and Deep Colour up to 48-bit
- Supports 4K resolutions including:
3840x2160@24/25/30Hz,
4096x2160@24/25/30Hz, 3840x2160@50/60Hz (4:4:4) & 4096x2160@50/60Hz (4:4:4)
- Supports pass-through of HD audio formats: LPCM 2/5.1/7.1CH, Dolby Digital 2/5.1CH, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos and DTS-HD Master Audio
- Supports OAR (Optical Audio Return) and DAC (Digital to Analog Conversion) audio balance conversion
- Support optical sampling rates up to 48kHz
- Internal 4K UHD Test Pattern Generator for on-site local display testing
- Integrated EDID management
- OSD with instant I/O resolution display

Vertrieb / Distributor:

VIDELCO Europe GmbH – Professionelle Audio-, Video-, Medien-Technik
Fon: +49 (0)2102 / 86 39-00 • Fax: +49 (0)2102 / 86 39-17 • info@videlco.eu • www.videlco.eu


VIDELCO
Europe GmbH

Matrices

Audio

Extenders

Switchers & Splitters

Scalers & Converters

Other AV