

PU 514-L-KIT HDBase™ LITE Extender Kit


HDBase™ LITE Extender Kit with 2-way IR (up to 60m)



The PU-514-KIT allows uncompressed HDMI, and 2-way IR signals to be transmitted over a Single CAT5e/6/7 cable to distances of up to 60m. Utilise the USB power output from a TV as an optional way of powering the PU-514L-RX receiver unit alternative to a mains power supply.

FEATURES

- HDMI 1.4 with 3D, 4Kx2K support, HDCP and DVI compliant
- Supports HDMI 1.4 (including HDCP) over a single CAT5e/6/7 up to 60m
- Complies with HDBase™- Lite specifications
- Full HD resolution support (1080p@60Hz/36-bit), 3D over 60m, 4Kx2K over 40m and PC resolution support (VGA to WUXGA) over CAT5e/6 cable
- HDMI input up to 15m with 8-bit deep colour, or 10m with 12-bit deep colour
- Supports HDMI output up to 15m with 8/12-bit deep colour
- Supports 2-way IR
- Supports High Definition LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio transmission
- Choose to power the PU-514L-RX via the USB output from a TV (Cable available separately - APC-USB):
 - * Please note the performance and consistency of USB power outputs from TV's can vary and cannot be guaranteed by CYP.



SPECIFICATIONS

PU-514L-RX

Inputs	1x RJ45 [1x HDMI & Propriety Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Receiver]
Outputs	1x HDMI [1x HDMI Uncompressed AV and Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Emitter]
PSU:	5V/2.6A
Dimensions	55mm [W] x 52mm [D] x 22mm [H]
Net Weight	60g

PU-514L-TX

Inputs	1x HDMI [1x HDMI Uncompressed AV and Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Receiver]
Outputs	1x RJ45 [1x HDBase™ Lite HDMI & Propriety Data] 1x 3.5mm Stereo mini-jack [1x Infra Red Emitter]
PSU:	5V/2.6A
Dimensions	55mm [W] x 83mm [D] x 22mm [H]
Net Weight	60g

