

4-Port 10/100Base-TX + 2-Port 100Base-FX Industrial Fast Ethernet Switch



New slim type with more practicability and convenience

PLANET releases the advanced industrial hardened Ethernet Switch with new slim type, IP-30 metal case: ISW-621 / ISW-621S15. Each of them equips with 4 10/100Base-TX Auto-negotiation ports. The ISW-621 has 2 100Base-FX multi-mode SC interfaces for transmission distance up to 2km, and the ISW-621S15 has 2 100Base-FX single-mode SC interfaces for transmission distance up to 15km, both of them operate reliably in Heavy Industrial demanding environments. Meanwhile, the compact, IP-30 standard metal case allows either DIN rail or wall mounting for efficient use of cabinet space.

Stable operate performance under difficult environments

The ISW-621 / ISW-621S15 provide a high level of immunity against electromagnetic interference and heavy electrical surges which are usually found on plant floors or in curb side traffic control cabinets. Being able to operate under the temperature range from -10 to 60 Degree C coupled with hazardous location certification (Class 1 Division 2), the ISW-621 / ISW-621S15 can be placed in almost any difficult environment. The ISW-621 / ISW-621S15 also possess an integrated power supply source with wide range of voltages (12 to 48V DC) for worldwide high availability applications requiring dual or backup power inputs.

Robust Switch performance

The ISW-621 / ISW-621S15 each provides 4 10/100Base-TX Ethernet ports and 2 100Base-FX optic-fiber SC interfaces, and boasts a high performance switch architecture that is capable of providing non-blocking switch fabric and wire-speed throughput as high as 1.2Gbps. With 2K MAC Address table, they offer wire-speed packets transfer performance without risk of packet loss. The Flow Control function allows the ISW-621 / ISW-621S15 for fast and reliable data transfer.

All of the RJ-45 copper interfaces in the ISW-621 / ISW-621S15 support 10/100Mbps Auto-Negotiation for optimal speed detection through RJ-45 Category 3, 4 or 5 cables. The standard Auto-MDI/MDI-X support can detect the type of connection to any Ethernet device without requiring special straight or crossover cables.

KEY FEATURES

PHYSICAL PORT

- 4-Port 10/100Base-TX RJ-45 with auto MDI/MDI-X function
- 2-Port 100Base-FX interfaces for up to 2km (Multi-mode fiber 50/125µm) on ISW-621
- 2-Port 100Base-FX interfaces for up to 15km (Single-mode fiber 9/125µm) on ISW-621S15

LAYER 2 FEATURES

- Complies with IEEE 802.3, IEEE 802.3u 10/100Base-TX, 100Base-FX Ethernet standard
- Supports Auto-negotiation and 10/100Mbps half / full duplex mode for each copper port
- High performance Store and Forward architecture, broadcast storm control, runt/CRC filtering eliminates erroneous packets to optimize the network bandwidth
- Prevents packet loss with back pressure (Half-Duplex) and IEEE 802.3x PAUSE frame flow control (Full-Duplex)
- Backplane (Switching Fabric): 1.2Gbps
- Integrated address look-up engine, support 2K absolute MAC addresses
- 1 Mbit on-chip frame buffer
- Automatic address learning and address aging
- CSMA/CD Protocol


INDUSTRIAL CASE / INSTALLATION

- IP-30 Metal case / Protection
- DIN Rail and Wall Mount Design
- 12 to 48V DC, redundant power with polarity reverse protect function and connective removable terminal block for master and slave power
- Supports EFT protection 6000 VDC for power line
- Supports 6000 VDC Ethernet ESD protection
- -10 to 60 Degree C operation temperature

APPLICATIONS

Industrial area Switch for data collect and forward

The ISW-621 / ISW-621S15 equip with 4 10/100Mbps ports that offers auto MDI / MDIX feature, 2 100Base-FX optic-fiber SC interfaces, 1.2Gbps non-blocking switch fabric, and the 2K MAC Address table so that they can perform wire-speed packets transfer without risk of packet loss. The ISW-621 / ISW-621S15 with the slim type IP 30 metal shape is ideal for most Heavy Industrial demanding environments.



SPECIFICATION

Product	4-Port 10/100Base-TX + 2-Port 100Base-FX Industrial Fast Ethernet Switch		
Model	ISW-621	ISW-621S15	
Hardware Specification			
Copper	Ports	4 x 10/100Base-TX, Auto-negotiation, Auto-MDI/MDI-X	
	Cable	10Base-T : 2-pair UTP Cat. 3, 4, 5 cable (100meters, max.) 100Base-TX : 2-pair UTP Cat. 5 cable (100meters, max.)	
Optical	Port	2 x 100Base-FX	
	Cable	50/125 µm fiber	9/125 µm fiber
	Mode	Multi-mode	Single-mode
	Distance	2km	15km
	Frequency	1300nm	1310nm
	Launch Power	Max. -14dBm, Min. -19dBm	Max. -7dBm, Min. -20dBm
	Receive Sensitivity	-34.5dBm	-28dBm
Max. Input Power	-14dBm	-8dBm	
Dimension (W x D x H)	135 x 97 x 32 mm		
Weight	442g		
Power Requirement	12~48V DC, Redundant power with polarity reverse protection function		
Power Consumption / Dissipation	11.6 Watts / 40BTU		
Installation	DIN rail kit / wall mount ear		
Alarm	Provides one relay output for power fail Alarm Relay current carry ability: 1A @ DC 24V		
Switch Specification			
Switch Processing Scheme	Store-and-Forward		
Address Table	2K entries		
Buffer	1Mbit		
Flow Control	Back pressure for half duplex IEEE 802.3x Pause Frame for full duplex		
Switch Fabric	1.2Gbps		
Throughput (Packet Per Second)	0.89Mpps @ 64Bytes		
Standards Conformance			
Standards Compliance	IEEE 802.3 Ethernet, 10Base-T IEEE 802.3u Fast Ethernet, 100Base-TX, 100Base-FX IEEE 802.3x Full-duplex flow control		
Temperature	Operating: -10~60 Degree C Storage: -40~85 Degree C		
Humidity Operating	Operating: 5~90%, Storage: 5~90% (Non-condensing)		
Regulation Compliance	FCC Part 15 Class A, CE		
Stability Testing	IEC60068-2-32(Free fall) IEC60068-2-27(Shock) IEC60068-2-6(Vibration)		

ORDERING INFORMATION

ISW-621	4+2 100FX Port Multi-mode Industrial Ethernet Switch - 2km (-10~60 Degree C operate temperature)
ISW-621S15	4+2 100FX Port Single-mode Industrial Ethernet Switch - 15km (-10~60 Degree C operate temperature)

RELATED PRODUCTS

ISW-511	4+1 100FX Port Multi-mode Industrial Ethernet Switch - 2km (-10~60 Degree C operate temperature)
ISW-511S15	4+1 100FX Port Single-mode Industrial Ethernet Switch - 15km (-10~60 Degree C operate temperature)
ISW-511 T	4+1 100FX Port Multi-mode Industrial Ethernet Switch - 2km (-40~75 Degree C operate temperature)
ISW-511 TS15	4+1 100FX Port Single-mode Industrial Ethernet Switch - 15km (-40~75 Degree C operate temperature)
ISW-621 T	4+2 100FX Port Multi-mode Industrial Ethernet Switch - 2km (-40~75 Degree C operate temperature)
ISW-621 TS15	4+2 100FX Port Single-mode Industrial Ethernet Switch - 15km (-40~75 Degree C operate temperature)



PLANET reserves the right to change specifications without prior notice.