

Feature

- Extends HDMI, USB, Audio and RS-232C over one CAT5e/CAT6 cable
- Up to 4K(3840X2160@30Hz) at 100m
- Remote control: RS-232C x 1, Audio x 1(Speaker, Microphone)
- Very low latency (<10ms)
- Support USB 2.0
 - TX: USB A type x 1
 - RX: USB A type x 3 (Keyboard, Mouse, USB flash memory)



Order number: 8634-0043-01

Transmitter

Receiver

Signal type/Connectors

1xHDMI via type A female,
1xLoop out HDMI via type A female
1xUSB2.0 type A female
1xMIC, 1xLine out
1xRS-232 9pin female
1xRJ45 female

1xHDMI via type A female
3xUSB2.0 type A female
1xAudio, 1xLine out
1xRS-232 9pin female
1xRJ45 female

Video bandwidth (Pixel clock) 297MHz

297MHz

Resolution range Up to 4K (3840x2160@30Hz)

Up to 4K (3840x2160@30Hz)

General

Power supply 1 x External power supply
100~240V DC 12V,3.33A

Power consumption (Max.) 7.5W

Enclosure type Metal

Enclosure dimensions TX: 205W x 103D x 30H(mm)
RX: 205W x 103D x 30H(mm)

Certifications CE, FCC

Environment Operating temperature range: 0°C~50°C
Storage temperature range: -20°C~70°C